

Prelude T-24 XL²



Short Description

Suspended ceiling substructure components for indoor use. Top quality Exposed 24 mm T- grid system. Fire punched, made of galvanized steel and coated with paint. Click system makes it easy and safe to install. Universal Prelude main runners are universal to 3 systems TLX, TL & XL². Prelude is unique in being rotary stitched, so the main runner remains stable during installation.

Dimensions

Dimensions	
Width x Length	Height
Universal Main runner Prelude 24 Peakform:	
24 x 3000 mm (White)	43 mm
24 x 3600 mm (White, Silver Grey, Black)	43 mm
.	
Cross tee Prelude 24 XL ² :	
24 x 1800 mm (White)	38 mm
24 x 1200 mm (White, Silver Grey, Black)	38 mm
24 x 600 mm (White, Silver Grey, Black)	30 mm
.	
Perimeter trim:	
22 x 3000 mm (White)	22 mm
19 x 3000 mm (Silver Grey, Black)	24 mm
.	
Shadowline:	
(15+15) x 3050 (White)	(8+25) mm

Packaging

Package Type Carton

Fire Properties

Reaction to Fire		
Property	Value	According to
Reaction to Fire, Euroclass	A1	EN 13964:2014

The grid is able to cope with expansion due to heat in a fire and remain flat and stable so that no large gaps and cracks appear between grid and tile.

